

Worksurfaces and Side Panels (Gables)

- Worksurface and side panels are 1" (25 mm) thick, solid core, 45 lbs/ft³ density particle board, finished on both sides with thermofused laminate, offering premium quality abrasion and stain resistant surfaces.
- Worksurfaces are edged on all four sides.
- Worksurfaces and side panels are edged with 1.5mm thick edges, improving user comfort and product durability.
- Side panels edged on bottom for additional strength and to seal out moisture.
- Side panels include height adjustable floor levelers; floor levelers offer additional space between side panels and floor, minimizing moisture damage from floor.
- Floor levelers have square bodies with rounded bottoms and are height adjustable from 5/8" (16 mm) to 1 5/8" (41 mm) high.
- Side panels on desk shells and corner units are interchangeable, allowing for onsite reconfigurations.
- Underside of worksurfaces are pre-drilled with positioning holes to accept PanelX above worksurface divider panels.

Back Panels

- Back panels are 5/8" (16 mm) thick, solid core, 45 lbs/ft³ density particle board, finished on both sides with thermofused laminate.
- Full height back panels standard on desks with box/box/file or file/file pedestals.
- 18" height back panels available on desks with box/file pedestals.
- 12" height back panels available on desk shells, extended corner units, and shaped tables.
- Flush back panels standard on returns and connecting tops.
- Flush back panels standard on 20" (508 mm), 24" (610 mm), and 30" (762 mm) deep desk shells, corner units, and extended corner units.
- Recessed 6" (152 mm) back panels standard on 30" (762 mm) deep assembled desks.
- Recessed 12" (305 mm) back panels standard on 36" (914 mm) deep assembled desks.
- Full height back panels standard on 36" (914 mm), 42" (1067 mm), and 48" (1219 mm) high hutches.

Pedestals and Drawers

- Drawer fronts are 5/8" (16 mm) thick, solid core particle board, finished on both sides with thermofused laminate.
- Drawer fronts have 1.5mm thick edging on all four sides.
- Five sided drawer construction offers strength and durability.
- Interior drawer construction is made with 1/2" (13 mm) black laminate sides, back and front, and 1/8" (3 mm) black hardboard bottom.
- Pedestals standard with side pull out drawers or optional pull handles.
- Lateral file drawers open with front pull handles.
- Box drawers, file drawers, and lateral file drawers operate with full extension ball bearing suspension slides for smooth and quiet operation.
- Box drawers are mounted on full suspension slides with 100 lbs / 45 kg weight capacity.
- File drawers are mounted on full suspension slides with 100 lbs / 45 kg weight capacity.
- Lateral file drawers are mounted on full suspension slides with 150 lbs / 68 kg weight capacity.
- Pedestal Box drawers standard with molded plastic pencil tray (one per unit).
- File drawers and lateral file drawers include file supports, accepting front-to-back letter and side-to-side legal filing.
- File drawers and lateral file drawers, optional file supports available for side-to-side letter filing.

Doors

- Laminated doors are 5/8" (16 mm) thick, solid core particle board finished on both sides with thermofused laminate.
- Laminated doors have 1.5mm thick edging on all four sides.
- Glazed doors are assembled in a framed exterior with frosted glazed interior.
- Cabinet doors open with pull handles or door overhang (located on bottom door edge).
- Cabinet doors operate on easy closing hinges.
- 71in/1803mm, 77in/1956mm and 83in/2108mm height cabinets, pull handles are placed at matching height to 65in/1651mm height cabinets.

Edges

- All edges are scuff resistant.
- Edges are applied to components using state-of-the-art automated machinery.
- All components standard with matching edging.

Locks

- Locks standard with interchangeable lock core.
- Locks standard with collapsible key, preventing damage to key.
- Lock core can be changed, allowing multiple units to be keyed alike or allowing multiple units in a common area to be keyed differently (100 different cores available).
- Locks standard on box/file pedestals.
- Locks standard on box/box/file pedestals.
- Locks standard on file/file pedestals.
- Locking doors are standard on selected laminate door cabinets.
- Locks standard on 2 drawer, 3 drawer, 4 drawer, and 5 drawer lateral files.
- Identical lock numbers are automatically supplied on the same unit.
- Core removable key available, master key available.
- Large or Express Program orders may include repetition of same key numbers as locks are randomly installed, unless otherwise specified.
- Optional locks available on laminate and glazed hutch doors, which are standard non-locking.
- Optional locks available on mini-storage cabinets and selected mini-lateral files.
- Optional locks available on glazed cabinet doors, which are standard non-locking.
- Optional locks available on 6in/152mm wide personal wardrobe tower doors.
- Optional locks available on cabinet doors with door overhang.

Hutches

- Hutches mount onto base units without mechanical fasteners; two sided tape or "Velcro" strips are provided, allowing installer to attach hutches to base units.

Grommets

- Grommets standard on all returns, connecting tops, corner units, extended corner units, and selected shaped worksurfaces.
- Optional factory installed grommets available for all worksurface and side panels (gables).
- For specific products that require a second grommet location, see page "grommet placement options".

Power/Data Modules

- Optional power/data module can be installed on any worksurface.

Packaging

- Units packaged using corrugated cartons; or shrink wrap and cardboard protectors.
- Worksurface edges and corners reinforced with edge and corner protectors.
- Wood-strapping supports the bottom portion of assembled units.

Thicknesses (Thermofused Laminate - TFL)

Worksurfaces:	1" (25 mm) thick.
Side Panels (Gables):	1" (25 mm) thick.
Back Panels:	5/8" (16 mm) thick.
Drawer Fronts:	5/8" (16 mm) thick.
Doors:	5/8" (16 mm) thick.

Thicknesses (High Pressure - HPL)

HPL option available on worksurfaces.
High pressure worksurfaces standard with high pressure laminate on top and brown backer on bottom.
Add 1/16" (1.6 mm) to overall worksurface thickness.

Industry Standards

- Components meet ANSI/BIFMA standards.

Size, Thickness, & Weight

- Widths, depths, heights, volumes, weights, and laminate/edge thicknesses are nominal and not exact.
- Heights include floor levelers (some exceptions apply).

Note: We are constantly upgrading our products, visit ofgo.com for the most up-to-date product specifications available.